




305001

DIVE MINI

Underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone gasket, 24V DC remote driver needed, with 1 x COB LED. IP 68 rating.



! THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
cob led	M 30°	607	75.87

Finish color options:

Stainless Steel

remote driver selection						
brand	manufacturer code	type	watt	IP rate	numbers of fixtures	
Meanwell	LPV-20-24	constant voltage 24V DC	20W	IP67	min 1 - max 2	
Meanwell	LPV-35-24	constant voltage 24V DC	35W	IP67	min 1 - max 3	
Meanwell	LPV-60-24	constant voltage 24V DC	60W	IP67	min 1 - max 6	

Technical features



Technical data

Wattage	8 WATT
IP Rating	IP68 - 1 METERS DEPTH
IK Rating	IK09
Material	Completely made in stainless steel AISI 316 L marine grade
Light source	NR. 1x8W COB LED
Screws	Stainless steel
Remote driver	24V DC NEEDED
Gasket	Silicone rubber
Glass	Tempered
Cable gland	PG11 Cable gland made copper with nickel-coated
Power cable	3 mt. neoprene power cable included
Gross weight	1,10 Kg

