


203006

# LINE SLIGHT 35

Linear ground-recessed luminaire for outdoor installation, length 1.080mm, Phospho-chromatised and polyester powder coated extruded copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gaskets, stainless steel recessing sleeve. Special optics with “invisa-light” technology. Built-in LED driver 220-240V 50-60Hz, with 35 CREE XP-G2 LED. IP67 rating.



### MINIATURIZED


STANDARD  
HYDROLINE

HYDROLINE  
SLIGHT



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	18°	3.502	89.79
high-power led	36°	3.526	85.29
<b>4000°K neutral-white</b>			
high-power led	18°	3.648	93.54
high-power led	36°	3.465	88.86

### Finish color options:

 Stainless Steel

### Technical features



### Technical data

Wattage	39 WATT
IP Rating	IP67
IK Rating	IK09
Material	High corrosion resistance extruded copper-free aluminum body
Trim	Stainless steel AISI 304
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	NR. 35 x 1 W CREE “XP-G2” LED
Optics	Special optics with “invisa-light” technology
Screws	Stainless steel
Recessing sleeve	Stainless steel
Transformer	Electronic power supply 220/240V 50/60Hz built-in
Static weight resistance	Max 5000 Kg
Gasket	Silicone rubber
Glass	Tempered
Cable gland	Double M20
Power cable	1 mt. neoprene power cable included
Gross weight	7,00 Kg



### High visual comfort

