





303001


POOL MEDIUM

Swimming-pool underwater luminaire, round shape, wall-recessed, completely made in stainless steel AISI 316L, polypropylene housing for recess. 24V remote driver needed, with 6 OSRAM LED. IP 68 rating.



THIS LUMINAIRE IS SUITABLE ONLY FOR UNDERWATER INSTALLATION



| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|--------------------------|---|-------------------|------------------------|
| 3000°K warm-white | | | |
| high-power led |  30° | 1.200 | 100.00 |

Finish color options:

 Stainless Steel

remote driver selection

| brand | manufacturer code | type | watt | IP rate | numbers of fixtures |
|----------|-------------------|-------------------------|------|---------|---------------------|
| Meanwell | LPV-20-24 | constant voltage 24V DC | 20W | IP67 | 1 |
| Meanwell | LPV-35-24 | constant voltage 24V DC | 35W | IP67 | min 1 - max 2 |
| Meanwell | LPV-60-24 | constant voltage 24V DC | 60W | IP67 | min 1 - max 4 |
| Meanwell | LPV-100-24 | constant voltage 24V DC | 100W | IP67 | min 1 - max 7 |

Technical features



Technical data

| | |
|----------------|--|
| Wattage | 12 WATT |
| IP Rating | IP68 - 1 METERS DEPTH |
| IK Rating | IK09 |
| Material | Completely made in stainless steel AISI 316 L marine grade |
| Trim | Stainless steel AISI 316 L marine grade |
| Light source | NR. 6 x 2W OSRAM LED |
| Screws | Stainless steel |
| Remote driver | 24V DC NEEDED |
| Gasket | EPDM rubber |
| Glass | Tempered |
| Cable gland | PG11 made in nickel-plated brass. |
| Power cable | 3 mt. neoprene power cable included |
| Recess housing | Polypropylene material |
| Gross weight | 2,00 Kg |

